



Afmetingen

Type	Lengte (mm)	Breedte (mm)	Hoogte (mm)
LFH	540	600	600
XLFH	690	720	680

Materialen

Onderdeel	Materiaal
Behuizing	Roestvrij staal
Blad	PA66
Element	Roestvast stalen buiselementen Ex e vinnen
Ex d behuizing	geanodiseerd geëxtrudeerd aluminium

Certificering

ATEX	IECEx
Ex II 2 G/D Ex h	Ex db eb h IIB+H2 T3 to T4 Gb
Ex db eb IIB+H2 T3 to T4 Gb	Ex tb IIIC T200 to T135°C Db
Ex tb IIIC T200 to T135°C Db	

Type tabel

Type	Spanning (V)	Vermogen(kW)	Maximumstroom (A)	Air Delta T (°C/°F)
LFH-T4	440	9	13	26/47
	400	7,5	12	22/40
	230 (3Ph)	7,5	12	22/40
LFH-T3	440	15	21	36/68
	400	12,5	19	32/58
	230 (3Ph)	12,5	33	32/58
XLFH-T4	440	14,5	20	32/58
	400	12	18	26/47
	230 (3Ph)	12	32	26/47
XLFH-T3	440	24	32	46/82
	400	20	30	38/68
	230 (3Ph)	20	55	38/68

1. LFH en XLFH ventilatorkachels zijn ook verkrijgbaar in 380V, 415V, 480V, 600V en 690V opties.
2. Maximaalstroom is inclusief inschakelstroom van de motor
3. Air Delta T waardes genomen bij het stopcontact.